

## **8000D Linerless Desktop**

Media Type	Label	✓
	Receipt	
	Tag	
	Wristband	
Material Type	Paper	✓
	Synthetic	
Printing Technology	Direct Thermal (no Ribbon Required)	<b>✓</b>
	Thermal Transfer (Ribbon Required)	
Finish	Matte	
	Gloss	1

Adhesive Type	Permanent	✓
	Removable	
	No Adhesive	
Environment	Indoor	✓
	Outdoor	
Properties	Cold Temperature	✓
	Deep Freeze	
	High Temperature	
	Ultra High Temperature	
	High Tack	
	Chemical Resistance	-

Note: Will require a linerless platen roller and cutter for the printer and is not recommended for applications involving chemicals.

## **Additional Features**

- Specially designed adhesive, approved for use in Zebra desktop printers with cutter.
- No ribbon required for direct thermal printing, therefore only one stock item needed
- Absence of a liner allows for more labels per roll and no waste having both environmental and safety implications in some applications
- Good scratch and smear resistance
- Excellent print quality when used in a Zebra linerless printer
- BPA free
- Latex free adhesive

## **Suggested Applications**

- Product and price labelling in retail applications
- Postal applications
- Work in progress labelling
- Applications that do not allow the use of a liner

## **Technical Specifications**

	Description	Caliper
Facestock	Smooth white silicone topcoated paper	82 +/- 8 microns
Adhesive	Permanent rubber adhesive	16 microns
	Total	98 microns ±10%



**Recommended Zebra Printers:** Zebra linerless desktop printers

**Minimum Application Temperature:** 

When the label is applied, the environment and surface should be above this temperature

+8°C

**Service Temperature Range:** 

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-10°C to 70°C

**Recommended Storage Conditions:** 

Storage of product before use

6 months duration when stored at 22°C at 50% RH

Rolls must be stored below 35C

Relative humidity must be less than 85% Rolls must be stored indoors and away from

direct sunlight

Rolls must be kept in their original

packaging

**Expected Life Span in Application:** 

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, 1 to 2 years

Compliance	
REACH (EU Directive EC 19007/2006)	✓
RoHS (EU Directive 2002/62)	✓
EN71-3 Safety of Toys and the UK Packaging Regulations 1998	✓
BPA & BPS Free	✓

For testing please order from ZipShip, or contact your supplies sales representative. The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application