

8000D Linerless Mobile

	Label	✓
Media Type	Receipt	
	Tag	
	Wristband	
Material Type	Paper	✓
	Synthetic	
Printing Technology	Direct Thermal (no Ribbon Required)	√
	Thermal Transfer (Ribbon Required)	
Finish	Matte	
	Gloss	✓

	Permanent	✓
Adhesive Type	Removable	
3)	No Adhesive	
Environment	Indoor	✓
	Outdoor	
Properties	Cold Temperature	>
	Deep Freeze	
	High Temperature	
	Ultra High Temperature	
	High Tack	
	Chemical Resistance	-

Note: 10027368RM code. Not recommended for applications involving chemicals.

Additional Features

- Specially designed adhesive, for unwinding in Zebra mobile printers, approved for use in Zebra ZQ3 series printers.
- No ribbon required for direct thermal printing, therefore only one stock item needed
- Absence of a liner allows for more labels per roll and no waste having both environmental and safety implications in some applications
- Good scratch and smear resistance
- Excellent print quality when used in a Zebra linerless printer
- BPA free
- Latex free adhesive

Suggested Applications

- Postal applications
- Product and price labelling in retail applications
- Work in progress labelling
- Applications that do not allow the use of a liner

Technical Specifications

	Description		Caliper
Facestock	Smooth white silicone topcoated paper		76 +/- 8 microns
Adhesive	Permanent rubber adhesive		12 microns
	_1	Total	88 microns ±10%



Recommended Zebra Printers: Zebra ZQ3 series mobile printers

Minimum Application Temperature:

When the label is applied, the environment and surface should be above this temperature

+10°C

Service Temperature Range:

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-10°C to 60°C

Recommended Storage Conditions:

Storage of product before use

6 months duration when stored at 22°C at 50% RH

Rolls must be stored below 35C

Relative humidity must be less than 85% Rolls must be stored indoors and away from

direct sunlight

Rolls must be kept in their original

packaging

Expected Life Span in Application:

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, 1 to 2 years

Compliance	
REACH (EU Directive EC 19007/2006)	
RoHS (EU Directive 2002/62)	✓
BPA & BPS Free	✓

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application